



New 1/4" RULER FOOT

The 1/4" RULER FOOT was specifically designed to use with quilting rulers for ruler work. The key point of the foot is the 1/4" cup height which moves smoothly alongside the quilting ruler without allowing the ruler to slide over or under the foot. The needle drops a 1/4 inch away from the ruler to create the quilting line.



Part No. : **202-442-000**

1/4" RULER FOOT

For Low Shank Horizontal Rotary Hook Models
(7 mm maximum width)



Part No. : **202-441-009**

1/4" RULER FOOT

For High Shank Horizontal Rotary Hook Models
(9mm/7mm maximum width)



Part No. : **767-441-005**

1/4" RULER FOOT SET


For High Speed Straight Stitch Models (incl. Darning plate)



*Other than the parts shown in the images above, no other attachments are required

Point 1 Adjustable Presser Foot Height

You can adjust the height of the foot to match the fabric by turning the round nut on the foot.



Point 2 Front and Side of Foot are V-Shaped

The V-shaped gaps in the foot greatly improve visibility. The gaps on the front and side of the foot make it easier to see around the needle helping increase the accuracy of your work. The side gap is good for when using the sewing machine side on.



Point 3 Useful Marks on the Foot

Marks on the foot can be used to determine the center point of the foot, helping to create accurate ruler work designs!




Tips

- * Turn the hand wheel to lower the needle when the presser foot is raised and the foot is set to a high position. Please do not use the needle up/down button as the needle bar may hit the foot.
- * Use with the center needle position and the feed dogs down.
- * This foot cannot be used with sewing machines on which the presser bar automatically moves up and down when free-motion quilting.
- * When using some 7 mm low shank models, the larger type setscrew may hit the quilting ruler so changing to the smaller type setscrew as shown on the right is recommended:
- * Use with 4.5 mm thickness quilting rulers compatible with Janome sewing machines.
- * Using the straight stitch needle plate is recommended for better results when using high/low shank horizontal rotary hook models.



Needle up/down button



Smaller type setscrew

